

Model 8805 (e), 8810 (e), 8815 (e)  
File Number: E213134

COMPANY

3M COMPANY  
INDUSTRIAL ADHESIVES & TAPES DIV  
3M CENTER  
BLDG 230-3G-07  
SAINT PAUL, MN 55144-1001 United States

MODEL INFO

8805 (e), 8810 (e), 8815 (e) (e) - Dielectric strength of 26.3kV/mm after exposure to 40 hrs at 23° C and 50% R.H., 21.5kV/mm after exposure to 96 hrs at 35° C and 90% R.H.  
Acrylic transfer adhesive tape

COMPONENT INSULATING MATERIALS, MISCELLANEOUS	VALUE
Form of Shipment	sheets, rolls

GENERAL													
Color	Thk Type	Thk (mm)	Overall Thk (mm)	Number Conductors	Number Layers	Metal Thk (mm)	Flame Class	RTI Electrical	RTI Impact	RTI Strength	HWI	HAI	GWIT GV
NC, WT	Minimum	0.13-0.38					--	50	--	--	--	--	--



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."