



Model 468MP, 468MPL, 468MPF, 7955MP, 7955MPL, 7965MP, 9185MP, 9668MP, 9668MPL  
File Number: MH17478

COMPANY

3M COMPANY  
INDUSTRIAL ADHESIVES & TAPES DIV  
3M CENTER  
BLDG 230-3G-07  
SAINT PAUL, MN 55144-1001 United States

MODEL INFO

468MP, 468MPL, 468MPF, 7955MP, 7955MPL, 7965MP, 9185MP, 9668MP, 9668MPL

POLYMERIC ADHESIVE SYSTEMS		VALUE
Carrier	Adhesive Transfer Tapes with Adhesive 200MP	

RATINGS						
Surface	to Surface	Min Temp(C)	Max Temp(C)	Indoor Use	Outdoor Use	Surface Comment
Acrylic paint		-35	60	Yes	Yes	
Polyester paint		-35	60	Yes	Yes	
Urethane paint		-35	60	Yes	Yes	
Polycarbonate		-35	85	Yes	Yes	
Polyester Powder Paint		-35	100	Yes	Yes	
Acrylic/Urethane coated Polycarbonate		-35	85	Yes	Yes	
Polyethylene Terephthalate		-35	85	Yes	Yes	
Polyvinyl chloride		-35	75	Yes	Yes	

RATINGS						
Surface	to Surface	Min Temp(C)	Max Temp(C)	Indoor Use	Outdoor Use	Surface Comment
PCT		-35	85	Yes	Yes	When applied to a rigid surface

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."