



Model 4905, 4910  
File Number: E464624

COMPANY

3M COMPANY  
INDUSTRIAL ADHESIVES & TAPES DIV  
3M CENTER  
BLDG 230-3G-07  
SAINT PAUL, MN 55144-1001 United States

MODEL INFO

4905, 4910

SIGN ACCESSORIES	VALUE
Application	General Use Non-Electrical
Environmental Suitability	Wet, Damp or Dry Location

GENERAL			
Surface	Static Strength (psi)	Dynamic Bond Strength (psi)	Max Adhesive Temp (°C)
Polycarbonate	--	10	75
Aluminum	--	8	110
Acrylic/Polyurethane paint	--	10	90

Report Date: 2002-08-22



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear

<https://iq.ulprospector.com/en/profile?e=7282885>

adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."