



# tesa® 4122

## Product Information

Heavy duty carton sealing tape

### Product Description

tesa® 4122 is a premium packaging tape based on a very strong PVC backing and a natural rubber adhesive.

### Product Features

- Even heavy boxes or boxes with multilayer cardboard with high flap tension can be closed safely.

### Application Fields

tesa® 4122 is designed to close very heavy cartons or boxes with hazardous content. The tensile strength and elongation characteristics of the backing make the product resistant to high shock impacts.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |       |
|--------------------|----------------|-------------------|-------|
| • Backing material | PVC film       | • Total thickness | 88 µm |
| • Type of adhesive | natural rubber |                   |       |

### Properties/Performance Values

- |                       |         |                         |     |
|-----------------------|---------|-------------------------|-----|
| • Elongation at break | 100 %   | • Automatic application | Yes |
| • Tensile strength    | 65 N/cm | • Manual application    | Yes |

### Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 2 N/cm |
|---------|--------|



# tesa® 4122

## Product Information

### Additional Information

tesa® 4122 is easily printable. This product is only available in transparent. For brown/havana, please refer to tesa® 60422.

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04122>