

tesa Bodyguard® 50535 PV0

Product Information



Temporary protection tape for freshly painted surfaces on cars during transport

Product Description

tesa® 50535 PV0 Bodyguard is a perfect protection solution for freshly painted car bodies. Applied after the painting process, it provides reliable protection for painted surfaces susceptible to damage. It guarantees simple and efficient handling for manual or machine unwinding, fast application, and reliable residue-free removal.

Product Features

- Reliable protection of freshly painted surfaces
- Secure adhesion during transport
- Simple handling, and easy and residue-free removal
- Cost savings as polishing or repair after unmasking is eliminated
- Paint protection during outdoor storage for up to 12 months
- Easy disposal both the film and the adhesive system are environmentally friendly
- Due to good UV resistance and perfect paint compatibility, tesa® 50535 PV0 Bodyguard is a reliable way to protect cars during the transportation process.

Application Fields

tesa® 50535 PV0 Bodyguard is suitable for simple and reliable protection of freshly painted surfaces.

Example applications are:

• Flat or curved painted surfaces like car roofs, hoods etc.

To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing materialType of adhesive	polyolefinic film EVA	Total thickness	59 µm
Properties/Performance Values			
Tensile strength	24 N/cm	Suitable for die cutting	Yes
Chemical resistance	very good	UV resistance	52 weeks

Easy to remove



Yes

Alfonso XII, 579-585. 08918 Badalona Barcelona-España www.fustier.es +34 934 600 479 service@fustier.es





tesa Bodyguard® 50535 PV0

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit http://l.tesa.com/?ip=50535



Alfonso XII, 579-585. 08918 Badalona Barcelona-España www.fustier.es +34 934 600 479 service@fustier.es

