



tesa® 62204 colored



Product Information

Colored Filmic Packaging Tape

Product Description

tesa® 62204 is based on a stable sPVC backing, coated with a natural rubber adhesive.

Product Features

- The natural rubber adhesive mass offers excellent adhesion properties to a large number of different surfaces, both polar and non-polar.
- The adhesive also features a high tack and high initial bond, needing only a short time until reaching final adhesive power.
- Handling and usage is convenient, as tesa® 62204 can generally be used on all common desk dispensers and can be removed after use without leaving any residues behind.
- The tape is available in multiple different colors, making it ideal color-coding or marking.

Application Fields

- tesa® 62204 is ideally used to seal smaller objects such as boxes or cans
- The sealing tape is regularly used in bakeries or flower shops to seal small bags or wrap flower bouquets
- The tape is ideal for small-scale packaging, bundling, and closing
- Due to the availability of various bright colors, the tape can be used for marking or color-coding

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing material | PVC film | • Total thickness | 63 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|------|--------------------|---------|
| • Elongation at break | 80 % | • Tensile strength | 43 N/cm |
|-----------------------|------|--------------------|---------|

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 2 N/cm |
|---------|--------|



tesa® 62204 colored

Product Information

Additional Information

tesa® 62204 is available in red, blue, green and yellow.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=62204>